



TECHNICAL DATA SHEET

PRODUCT NAME: CRACK FILLER POWDER

Description

Crack Filler Powder was made to be mixed with Moisture Vapor Primer to create a semi-pourable flexible paste for filling small or large cracks prior to applying the Roll-Top, SprayCoat, or TerraStone System. It is a fine blend of additives that feathers to zero and adds to the flexibility of the Moisture Vapor Primer unlike silica sand. Crack repairs should never be guaranteed but Moisture Vapor Primer and Crack Filler Powder are a proven combination with a high success rate for repairing cracks.

Mixing Instructions

For a pourable mixture add 1 part of mixed Moisture Vapor Primer to 1 part Crack Filler Powder. Start with a small amount such as 12 oz. of mixed Moisture Vapor Primer to 12 oz. of Crack Filler Powder. Add more Crack Filler Powder up to 1 ½ parts as needed to create a thicker consistency. Mix using a drill and one gallon size mixing paddle. Mix only the amount that can be used within 15 -30 minutes. A larger or smaller batch can be made depending on the amount of crack repairs needed.

Application Instructions

Using a 2 qt. – 5 qt. mixing pail and a 4” putty knife, fill the cracks twice as deep as they are wide and remove any excess from the surface using the putty knife. The surface can then be primed with Moisture Vapor Primer if desired without waiting for the crack repairs to dry. The Moisture Vapor Primer can be applied over the repairs immediately or within 24 hours. After the primer dries or is barely tacky, patch over the cracks with FC Patch Fine using a 4” putty knife to fill any voids or sunken areas. Once the cracks are patched smooth, proceed installing the Roll-Top, SprayCoat, or TerraStone System. FC Patch Fine can also be sanded where needed to be sure the patches are smooth enough and feathered on the edges so they do not show through the coating system to follow. FC Patch Fine can also be used to fill any small holes or other surface imperfections.

Clean-up

If on skin, wash with soap and water. If in eyes, wash cautiously with water for several minutes. If irritation persists, seek medical attention.

Packaging

Crack Filler Powder is available in 10 lb. bags.

WARRANTY / DISCLAIMER

StoneCrete Systems warrants their products to be of the highest quality and free from defects. Our only warranty with respect to the products we sell, and our sole obligation, is to replace, or give credit for any of our products that prove to be defective. Any claim under this warranty must be made no later than one year from the date of purchase. StoneCrete Systems makes no other warranties expressed or implied, or statutory such as warranties of merchantability or fitness for a particular purpose. In no event shall StoneCrete Systems be liable for consequential or incidental damages.

The product buyer assumes all responsibility or risk whatsoever as to the result of the use of the products purchased from StoneCrete Systems, whether used singly or in combination with other products or substances. Our warranty excludes problems that may occur following product application due to moisture in a substrate, cracking or problems associated with the substrate on which the product or products are applied, or customer abuse. It is the responsibility of each product buyer to determine the suitability of each product for his or her particular purpose.